



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/775,490	02/09/2004	Patrick N. Nelson	MS1-1866US	1506
22801 7590 09/17/2009 LEE & HAYES, PLLC 601 W. RIVERSIDE AVENUE SUITE 1400 SPOKANE, WA 99201				
EXAMINER JONES, HEATHER RAE				
ART UNIT		PAPER NUMBER		
2621				
NOTIFICATION DATE		DELIVERY MODE		
09/17/2009		ELECTRONIC		

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Notice of the Office communication was sent electronically on above-indicated "Notification Date" to the following e-mail address(es):

lhptoms@leehayes.com

Office Action Summary

Application No.

10/775,490

Applicant(s)

NELSON, PATRICK N.

Examiner

HEATHER R. JONES

Art Unit

2621

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --
Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 30 June 2009.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 1-4 and 7-57 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 1-4 and 7-57 is/are rejected.
- 7) ☐ Claim(s) _____ is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☒ The drawing(s) filed on 09 February 2004 is/are: a) ☒ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some * c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
 2. ☐ Certified copies of the priority documents have been received in Application No. _____.
 3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

* See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- 1) ☒ Notice of References Cited (PTO-892)
- 2) ☐ Notice of Draftsperson's Patent Drawing Review (PTO-948)
- 3) ☒ Information Disclosure Statement(s) (PTO/S6108)
Paper No(s)/Mail Date 6/30/2009
- 4) ☐ Interview Summary (PTO-413)
Paper No(s)/Mail Date _____
- 5) ☐ Notice of Informal Patent Application
- 6) ☐ Other: _____

DETAILED ACTION

Continued Examination Under 37 CFR 1.114

1. A request for continued examination under 37 CFR 1.114, including the fee set forth in 37 CFR 1.17(e), was filed in this application after final rejection. Since this application is eligible for continued examination under 37 CFR 1.114, and the fee set forth in 37 CFR 1.17(e) has been timely paid, the finality of the previous Office action has been withdrawn pursuant to 37 CFR 1.114. Applicant's submission filed on June 30, 2009 has been entered.

Response to Arguments

2. Applicant's arguments with respect to claims 1-4 and 7-57 have been considered but are moot in view of the new ground(s) of rejection. Furthermore, the new ground(s) of rejection is based on claim amendments and a different interpretation of a previously applied reference.

Claim Rejections - 35 USC § 103

3. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

4. Claims 1-4 and 7-57 are rejected under 35 U.S.C. 103(a) as being unpatentable over Subramanian et al. (U.S. Patent 2005/0018775) in view of Griffiths (U.S. Patent 6,262,776).

Regarding claim 1, Subramanian et al. discloses a method, comprising:
determining, determining by a computing device, whether two or more samples of a presentation are processed by a first component of a pipeline at an expected time, the two or more samples comprising a first sample and a later processed second sample, wherein the determining comprises determining a first timing error for the first sample and a second timing error for the second sample (paragraph [0049] - the presentation time stamp for every B-picture is compared to the system time clock value, thereby meaning that two or more samples are processed since every B-picture is sampled and each one has its own result);
and requesting, by a computing device, a second component of the pipeline to alter the manner in which the second component processes a portion of the presentation if the at least one sample is not processed at the expected time (paragraph [0049] – if the PTS value and the STC value differ by more than a predetermined threshold, the video decoder drops the B-picture without decoding). However, Subramanian et al. fails to disclose that the second component of the pipeline alters the manner in which the second component processes a portion of the presentation of the presentation when the two or more samples are not processed at the expected time and when the first timing error is

greater than the second timing error, wherein the portion of the presentation comprises at least one succeeding sample to the two or more samples.

Referring to the Griffiths reference, Griffiths discloses a method for maintaining synchronization between audio and video comprising: determining whether at least two sample of a presentation is processed by a first component of a pipeline at an expected time; and wherein the second component of the pipeline alters the manner in which the second component processes a portion of the presentation of the presentation when the two or more samples are not processed at the expected time and when the first timing error is greater than the second timing error, wherein the portion of the presentation comprises at least one succeeding sample to the two or more samples (Fig. 11 – the next sample is altered; col. 18, lines 11-37 – frames are monitored and once the decoder gets too far behind then frames are altered in order to allow the decoder to resynchronize the video and audio; col. 18, lines 39-56 – various statistics on the timing of frames are monitored; col. 19, lines 11-36 - four situations are determined that include frames being too early and too late. Furthermore, the first and second samples are being compared in the fact that the system is monitoring the process of the decoding and once the frames are too early or too late other frames are altered. Griffiths discloses both situations of the first timing error being greater or less than the second timing error since Griffiths covers both the fact that frames can be too early and too late).

Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to have altered the succeeding sample in the presentation as disclosed by Griffiths in the method disclosed by Subramanian et al. in order to display the samples at the correct times as well as to maintain a synchronization between audio and video data so that the viewer can not detect any problems when synchronizing the video and audio).

Regarding claim 2, Subramanian et al. in view of Griffiths discloses all the limitations as previously discussed with respect to claim 1 including that the first component comprises a media sink (Subramanian et al.: paragraph [0049] – media sink – comparing the PTS value with the STC value).

Regarding claim 3, Subramanian et al. in view of Griffiths discloses all the limitations as previously discussed with respect to claim 1 including that the second component comprises a codec (Subramanian et al.: paragraph [0049] – the decoder drops the B-picture therefore, altering the manner in which the decoder processes the signal; Griffiths: Fig. 2).

Regarding claim 4, Subramanian et al. in view of Griffiths discloses all the limitations as previously discussed with respect to claim 1 including that the first component comprises a media sink and the second component comprises a codec (Subramanian et al.: paragraph [0049] – media sink – comparing the PTS value with the STC value; the decoder drops the B-picture therefore, altering the manner in which the decoder processes the signal; Griffiths: Fig. 2).

Regarding claim 7, Subramanian et al. in view of Griffiths discloses all the limitations as previously discussed with respect to claim 1 including that the portion of the presentation comprises a frame (Subramanian et al.: paragraph [0049] – one B-picture is a frame; Griffiths: Fig. 11 – the next sample is altered; col. 18, lines 11-37 – frames are monitored and once the decoder gets too far behind then frames are altered in order to allow the decoder to resynchronize the video and audio; col. 18, lines 39-56 – various statistics on the timing of frames are monitored; col. 19, lines 11-36 - four situations are determined that include frames being too early and too late).

Regarding claim 8, Subramanian et al. in view of Griffiths discloses all the limitations as previously discussed with respect to claim 1 including that determining whether the two or more samples are processed at the expected time comprises comparing a timing value in each of the two or more samples to a predetermined time frame associated with the presentation (Subramanian et al.: paragraph [0049] - the presentation time stamp for every B-picture is compared to the system time clock value; Griffiths: Fig. 11 – the next sample is altered; col. 18, lines 11-37 – frames are monitored and once the decoder gets too far behind then frames are altered in order to allow the decoder to resynchronize the video and audio; col. 18, lines 39-56 – various statistics on the timing of frames are monitored; col. 19, lines 11-36 - four situations are determined that include frames being too early and too late).

Regarding claim 9, Subramanian et al. discloses all the limitations as previously discussed with respect to claim 1 including that determining whether the two or more samples are processed at the expected time comprises comparing a timing value in each of the two or more samples to a presentation clock (Subramanian et al.: paragraph [0049] - the presentation time stamp for every B-picture is compared to the system time clock value; Griffiths: Fig. 11 – the next sample is altered; col. 18, lines 11-37 – frames are monitored and once the decoder gets too far behind then frames are altered in order to allow the decoder to resynchronize the video and audio; col. 18, lines 39-56 – various statistics on the timing of frames are monitored; col. 19, lines 11-36 - four situations are determined that include frames being too early and too late).

Regarding claim 10, Subramanian et al. in view of Griffiths discloses all the limitations as previously discussed with respect to claim 1 including that determining whether the two or more samples are processed at the expected time comprises determining whether a respective timing value in the two or more samples was processed by the first component at the time specified by the respective timing value (Subramanian et al.: paragraph [0049] - the presentation time stamp for every B-picture is compared to the system time clock value; Griffiths: Fig. 11 – the next sample is altered; col. 18, lines 11-37 – frames are monitored and once the decoder gets too far behind then frames are altered in order to allow the decoder to resynchronize the video and audio; col. 18, lines 39-56 – various statistics on the timing of frames are monitored; col. 19, lines

11-36 - four situations are determined that include frames being too early and too late).

Regarding claim **11**, Subramanian et al. in view of Griffiths discloses all the limitations as previously discussed with respect to claim 1 including that determining whether the two or more samples are processed at the expected time comprises determining whether a respective timing value in each of the two or more samples was processed by the first component within a given time of a time specified by the respective timing value (Subramanian et al.: paragraph [0049] - the presentation time stamp for every B-picture is compared to the system time clock value; Griffiths: Fig. 11 – the next sample is altered; col. 18, lines 11-37 – frames are monitored and once the decoder gets too far behind then frames are altered in order to allow the decoder to resynchronize the video and audio; col. 18, lines 39-56 – various statistics on the timing of frames are monitored; col. 19, lines 11-36 - four situations are determined that include frames being too early and too late).

Regarding claim **12**, Subramanian et al. in view of Griffiths discloses all the limitations as previously discussed with respect to claim 1 including determining whether the two or more samples are processed at the expected time comprises determining if the first sample is processed by the first component at a first expected time and determining if the second sample is processed by the first component at a second expected time (Subramanian et al.: paragraph [0049] - the presentation time stamp for every B-picture is compared

to the system time clock value and is processed if the PTS value and the STC value differ by less than a predetermined threshold; Griffiths: Fig. 11 – the next sample is altered; col. 18, lines 11-37 – frames are monitored and once the decoder gets too far behind then frames are altered in order to allow the decoder to resynchronize the video and audio; col. 18, lines 39-56 – various statistics on the timing of frames are monitored; col. 19, lines 11-36 - four situations are determined that include frames being too early and too late).

Regarding claim 13, Subramanian et al. in view of Griffiths discloses all the limitations as previously discussed with respect to claim 1, including determining whether the two or more samples are processed at the expected time comprises: determining the first timing error as a difference between a time at which the first sample is processed by the first component and a time at which the first sample is expected to be processed; and determining the second timing error as a difference between a time at which the second sample is processed by the first component and a time at which the first sample is expected to be processed (Subramanian et al.: paragraph [0049] - the presentation time stamp for every B-picture is compared to the system time clock value and is processed if the PTS value and the STC value differ by less than a predetermined threshold; Griffiths: Fig. 11 – the next sample is altered; col. 18, lines 11-37 – frames are monitored and once the decoder gets too far behind then frames are altered in order to allow the decoder to resynchronize the video and audio; col. 18, lines 39-56 –

various statistics on the timing of frames are monitored; col. 19, lines 11-36 - four situations are determined that include frames being too early and too late).

Regarding claim **14**, Subramanian et al. in view of Griffiths discloses all the limitations as previously discussed with respect to claim 1, including that the first sample comprising an associated first timing value and the second sample comprises an associated second timing value and wherein determining whether the two or more samples are processed at the expected time further comprises determining whether the first timing value more closely corresponds to a time at which the first sample is processed by the first component than the second timing value corresponds to a time at which the second sample is processed by the first component (Subramanian et al.: paragraph [0049] - the presentation time stamp for every B-picture is compared to the system time clock value and is processed if the PTS value and the STC value differ by less than a predetermined threshold; Griffiths: Fig. 11 – the next sample is altered; col. 18, lines 11-37 – frames are monitored and once the decoder gets too far behind then frames are altered in order to allow the decoder to resynchronize the video and audio; col. 18, lines 39-56 – various statistics on the timing of frames are monitored; col. 19, lines 11-36 - four situations are determined that include frames being too early and too late).

Regarding claim **15**, Subramanian et al. discloses all the limitations as previously discussed with respect to claim 1 including that altering the manner in which the second component processes a portion the presentation comprises

dropping the at least one succeeding sample (Griffits: Fig. 11 – the next sample is altered; col. 18, lines 11-37 – frames are monitored and once the decoder gets too far behind then frames are altered in order to allow the decoder to resynchronize the video and audio; col. 18, lines 39-56 – various statistics on the timing of frames are monitored; col. 19, lines 11-36 - four situations are determined that include frames being too early and too late).

Regarding claim 16, Subramanian et al. in view of Griffits discloses all the limitations as previously discussed with respect to claim 1 including that the portion of the presentation comprises a plurality of frames, altering the manner in which the second component processes the portion of the presentation comprises dropping a subset of the plurality of frames, wherein the subset comprises two or more frames (Griffits: Fig. 11 – the next sample is altered; col. 18, lines 11-37 – frames are monitored and once the decoder gets too far behind then frames are altered in order to allow the decoder to resynchronize the video and audio; col. 18, lines 39-56 – various statistics on the timing of frames are monitored; col. 19, lines 11-36 - four situations are determined that include frames being too early and too late).

Regarding claim 17, Subramanian et al. in view of Griffits discloses all the limitations as previously discussed with respect to claim 1 including that the first component is a media sink, the second component is a codec, and the wherein altering the manner in which the second component processes a portion of the presentation comprises dropping at least one frame of the presentation

(Subramanian et al.: paragraph [0049] – the presentation time stamp for every B-picture is compared to the system time clock value – media sink; if the PTS value and the STC value differ by more than a predetermined threshold, the video decoder drops the B-picture without decoding; Griffiths: Fig. 11 – the next sample is altered; col. 18, lines 11-37 – frames are monitored and once the decoder gets too far behind then frames are altered in order to allow the decoder to resynchronize the video and audio; col. 18, lines 39-56 – various statistics on the timing of frames are monitored; col. 19, lines 11-36 - four situations are determined that include frames being too early and too late).

Regarding claim **18**, Subramanian et al. in view of Griffiths discloses all the limitations as previously discussed with respect to claim 1 including that the pipeline comprises a media source, a media sink, and a topology of media processing nodes; the first component is a node in the topology; and the second component is the media sink (Subramanian et al.: paragraph [0049] – the presentation time stamp for every B-picture is compared to the system time clock value – media sink; if the PTS value and the STC value differ by more than a predetermined threshold, the video decoder drops the B-picture without decoding).

Regarding claim **19**, Subramanian et al. in view of Griffiths discloses all the limitations as previously discussed with respect to claim 1 including that the pipeline comprises a media source, a media sink, and a topology of media processing nodes; the first component is a node in the topology including a

codec; and the second component is the media sink (Subramanian et al.: paragraph [0049] – the presentation time stamp for every B-picture is compared to the system time clock value – media sink; if the PTS value and the STC value differ by more than a predetermined threshold, the video decoder drops the B-picture without decoding).

Regarding claim **20**, Subramanian et al. discloses a method, comprising: determining, by a computing device, if timeliness of sample processing in a multi-component pipeline is degrading, the determination being made based on processing times of a first sample and a second sample, the determination comprising calculating a first timing error for the first sample and a second timing error for the second sample (paragraph [0049] - the presentation time stamp for every B-picture is compared to the system time clock value; thereby meaning that two or more samples are processed since every B-picture is sampled and each one has its own result); altering, by the computing device, the manner in which a component in the multi-component pipeline processes a portion of the presentation when the timeliness of the sample processing is determined to be degrading (paragraph [0049] – if the PTS value and the STC value differ by more than a predetermined threshold, the video decoder drops the B-picture without decoding). However, Subramanian et al. fails to disclose comparing the processing times of a first sample and a second sample of the presentation and wherein the portion comprises one or more succeeding samples to the first and second sample.

Referring to the Griffiths reference, Griffiths discloses a method for maintaining synchronization between audio and video comprising: determining whether at least two sample of a presentation is processed by a first component of a pipeline at an expected time; and wherein the second component of the pipeline alters the manner in which the second component processes a portion of the presentation of the presentation when the two or more samples are not processed at the expected time, wherein the portion of the presentation comprises at least one succeeding sample to the two or more samples (Fig. 11 – the next sample is altered; col. 18, lines 11-37 – frames are monitored and once the decoder gets too far behind then frames are altered in order to allow the decoder to resynchronize the video and audio; col. 18, lines 39-56 – various statistics on the timing of frames are monitored; col. 19, lines 11-36 - four situations are determined that include frames being too early and too late. Furthermore, the first and second samples are being compared in the fact that the system is monitoring the process of the decoding and once the frames are too early or too late other frames are altered. Griffiths discloses both situations of the first timing error being greater or less than the second timing error since Griffiths covers both the fact that frames can be too early and too late).

Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to have altered the succeeding sample in the presentation as disclosed by Griffiths in the method disclosed by Subramanian et al. in order to display the samples at the correct times as well as to maintain a

synchronization between audio and video data so that the viewer can not detect any problems when synchronizing the video and audio).

Regarding claim **21**, Subramanian et al. in view of Griffiths discloses all the limitations as previously discussed with respect to claim 20 including that the processing times of the first and the second samples are determined relative to a single component in the pipeline (Subramanian et al.: paragraph [0049]; Griffiths: Fig. 11 – the next sample is altered; col. 18, lines 11-37 – frames are monitored and once the decoder gets too far behind then frames are altered in order to allow the decoder to resynchronize the video and audio; col. 18, lines 39-56 – various statistics on the timing of frames are monitored; col. 19, lines 11-36 - four situations are determined that include frames being too early and too late).

Regarding claim **22**, Subramanian et al. in view of Griffiths discloses all the limitations as previously discussed with respect to claim 20 including that the processing times of the first sample is determined relative to a first component in the multi-component pipeline and the processing times of the second sample is determined relative to a second component in the multi-component pipeline (Subramanian et al.: paragraph [0049]; Griffiths: Fig. 11 – the next sample is altered; col. 18, lines 11-37 – frames are monitored and once the decoder gets too far behind then frames are altered in order to allow the decoder to resynchronize the video and audio; col. 18, lines 39-56 – various statistics on the timing of frames are monitored; col. 19, lines 11-36 - four situations are determined that include frames being too early and too late).

Regarding claim **23**, Subramanian et al. in view of Griffiths discloses all the limitations as previously discussed with respect to claim 20 including that the processing times of the first and the second samples are determined using timing information in the first and second samples (paragraph [0049] - the presentation time stamp for every B-picture is compared to the system time clock value; Griffiths: Fig. 11 – the next sample is altered; col. 18, lines 11-37 – frames are monitored and once the decoder gets too far behind then frames are altered in order to allow the decoder to resynchronize the video and audio; col. 18, lines 39-56 – various statistics on the timing of frames are monitored; col. 19, lines 11-36 - four situations are determined that include frames being too early and too late).

Regarding claim **24**, Subramanian et al. in view of Griffiths discloses all the limitations as previously discussed with respect to claim 20 including that the processing times of the first and the second samples are determined using timing information in the first and second samples and a presentation clock (paragraph [0049] - the presentation time stamp for every B-picture is compared to the system time clock value; Griffiths: Fig. 11 – the next sample is altered; col. 18, lines 11-37 – frames are monitored and once the decoder gets too far behind then frames are altered in order to allow the decoder to resynchronize the video and audio; col. 18, lines 39-56 – various statistics on the timing of frames are monitored; col. 19, lines 11-36 - four situations are determined that include frames being too early and too late).

Regarding claim **25**, Subramanian et al. in view of Griffiths discloses all the limitations as previously discussed with respect to claim 20 including that the timeliness of the sample processing is determined based on: a first timing difference between a time specified in a timing value in the first sample and a time that the first sample is processed by the component in the multi-component pipeline; a second timing difference between a time specified by a timing value in the second sample and a time that the second sample is processed by the component in the multi-component pipeline (Subramanian et al.: paragraph [0049]; Griffiths: Fig. 11 – the next sample is altered; col. 18, lines 11-37 – frames are monitored and once the decoder gets too far behind then frames are altered in order to allow the decoder to resynchronize the video and audio; col. 18, lines 39-56 – various statistics on the timing of frames are monitored; col. 19, lines 11-36 - four situations are determined that include frames being too early and too late).

Regarding claim **26**, Subramanian et al. in view of Griffiths discloses all the limitations as previously discussed with respect to claim 20 including that the timeliness of the sample processing is determined based on: the first timing error being a difference between a time specified in a timing value in the first sample and a time that the first sample is processed by a first component in the multi-component pipeline; and the second timing error being a difference between a time specified by a timing value in the second sample and a time that the second sample is processed by a second component in the multi-component pipeline

(Subramanian et al.: paragraph [0049]; Griffiths: Fig. 11 – the next sample is altered; col. 18, lines 11-37 – frames are monitored and once the decoder gets too far behind then frames are altered in order to allow the decoder to resynchronize the video and audio; col. 18, lines 39-56 – various statistics on the timing of frames are monitored; col. 19, lines 11-36 - four situations are determined that include frames being too early and too late).

Regarding claim 27, Subramanian et al. in view of Griffiths discloses all the limitations as previously discussed with respect to claim 20 including that the timeliness of the sample processing is determined by: determining the first timing error being a difference between a time specified in a timing value in the first sample and a time that the first sample is processed by the component in the multi-component pipeline; determining the second timing error being a difference between a time specified by a timing value in the second sample and a time that the second sample is processed by the component in the multi-component pipeline, wherein the second sample is processed at a later time than the first sample; and determining that timeliness of sample processing is degrading if the second timing error is greater than the first timing error (Subramanian et al.: paragraph [0049]; Griffiths: Fig. 11 – the next sample is altered; col. 18, lines 11-37 – frames are monitored and once the decoder gets too far behind then frames are altered in order to allow the decoder to resynchronize the video and audio; col. 18, lines 39-56 – various statistics on the timing of frames are monitored;

col. 19, lines 11-36 - four situations are determined that include frames being too early and too late).

Regarding claim **28**, Subramanian et al. in view of Griffiths discloses all the limitations as previously discussed with respect to claim 20 including that the timeliness of the sample processing is determined by: determining the first timing error being a difference between a time specified in a timing value in the first sample and a time that the first sample is processed by a selected component in the multi-component pipeline; determining the second timing error being a difference between a time specified by a timing value in the second sample and a time the second sample is processed by the selected component, wherein the second sample is processed at a later time than the first sample; and determining that timeliness of sample processing is degrading if the second timing error is greater than the first timing error (Subramanian et al.: paragraph [0049]; Griffiths: Fig. 11 – the next sample is altered; col. 18, lines 11-37 – frames are monitored and once the decoder gets too far behind then frames are altered in order to allow the decoder to resynchronize the video and audio; col. 18, lines 39-56 – various statistics on the timing of frames are monitored; col. 19, lines 11-36 - four situations are determined that include frames being too early and too late).

Regarding claim **29**, Subramanian et al. in view of Griffiths discloses all the limitations as previously discussed with respect to claim 20 including that altering the manner in which the component in the multi-component pipeline processes a portion of the presentation comprises instructing the component to drop the one

or more succeeding samples (Griffits: Fig. 11 – the next sample is altered; col. 18, lines 11-37 – frames are monitored and once the decoder gets too far behind then frames are altered in order to allow the decoder to resynchronize the video and audio; col. 18, lines 39-56 – various statistics on the timing of frames are monitored; col. 19, lines 11-36 - four situations are determined that include frames being too early and too late).

Regarding claim **30**, Subramanian et al. in view of Griffits discloses all the limitations as previously discussed with respect to claim 20 including that altering the manner in which the component in the multi-component pipeline processes the portion of the presentation comprises instructing the component to drop each sample in a frame of the presentation (Subramanian et al.: paragraph [0049] – if the PTS value and the STC value differ by more than a predetermined threshold, the video decoder drops the B-picture without decoding; Griffits: Fig. 11 – the next sample is altered; col. 18, lines 11-37 – frames are monitored and once the decoder gets too far behind then frames are altered in order to allow the decoder to resynchronize the video and audio; col. 18, lines 39-56 – various statistics on the timing of frames are monitored; col. 19, lines 11-36 - four situations are determined that include frames being too early and too late).

Regarding claim **31**, Subramanian et al. in view of Griffits discloses all the limitations as previously discussed with respect to claim 20 including that each component comprises processor executable instructions executed by a processor (Subramanian et al.: Fig. 2).

Regarding claims **32-41**, these are apparatus claims corresponding to the method claims 1-4, 13-17, and 20. Therefore, claims 32-41 are analyzed and rejected as previously discussed with respect to claims 1-4, 13-17, and 20.

Regarding claims **42-46**, these are computer-readable medium claims corresponding to the method claims 1-4, 8, 15, and 20. Therefore, claims 42-46 are analyzed and rejected as previously discussed with respect to claims 1-4, 8, 15, and 20. Furthermore, Subramanian et al. comprises processor executable instructions executed by a processor (Fig. 2).

Regarding claims **47-51**, these are computer-readable medium claims corresponding to the method claims 1-4, 8, 13, and 15. Therefore, claims 47-51 are analyzed and rejected as previously discussed with respect to claims 1-4, 8, 13, and 15.

Regarding claim **52**, Subramanian et al. in view of Griffiths discloses all the limitations as previously discussed with respect to claim 1 including that the portion of the presentation comprises a third sample and a fourth sample (Griffiths: Fig. 11 – the next sample is altered; col. 18, lines 11-37 – frames are monitored and once the decoder gets too far behind then frames are altered in order to allow the decoder to resynchronize the video and audio; col. 18, lines 39-56 – various statistics on the timing of frames are monitored; col. 19, lines 11-36 – four situations are determined that include frames being too early and too late).

Regarding claim **53**, Subramanian et al. in view of Griffiths discloses all the limitations as previously discussed with respect to claims 1 and 13, including that

the method further comprises: if the second timing error is greater than the first timing error, further requesting the second component of the pipeline to alter the manner in which the second component processes the portion of the presentation, wherein the portion of the presentation comprises two or more succeeding samples to the at least one sample (Griffits: Fig. 11 – the next sample is altered; col. 18, lines 11-37 – frames are monitored and once the decoder gets too far behind then frames are altered in order to allow the decoder to resynchronize the video and audio; col. 18, lines 39-56 – various statistics on the timing of frames are monitored; col. 19, lines 11-36 - four situations are determined that include frames being too early and too late).

Regarding claim 54, Subramanian et al. in view of Griffits discloses all the limitations as previously discussed with respect to claims 1, 13, and 53 including that the two or more succeeding samples to the at least one sample are not consecutive samples (Griffits: Fig. 11, step 475 - all B frames are dropped regardless of where they are).

Regarding claim 55, Subramanian et al. in view of Griffits discloses all the limitations as previously discussed with respect to claim 20 including that the portion of the presentation comprises a third sample and a fourth sample (Griffits: Fig. 11 – the next sample is altered; col. 18, lines 11-37 – frames are monitored and once the decoder gets too far behind then frames are altered in order to allow the decoder to resynchronize the video and audio; col. 18, lines 39-56 –

various statistics on the timing of frames are monitored; col. 19, lines 11-36 - four situations are determined that include frames being too early and too late).

Regarding claim 56, Subramanian et al. in view of Griffiths discloses all the limitations as previously discussed with respect to claims 20 and 28 including that the method further comprises: if the timeliness of the sample processing is said determined to be degrading, further altering the manner in which the component processes the portion of the presentation, wherein the portion of the presentation comprises two or more succeeding samples to one or more of the first sample and the second sample (Griffiths: Fig. 11 – the next sample is altered; col. 18, lines 11-37 – frames are monitored and once the decoder gets too far behind then frames are altered in order to allow the decoder to resynchronize the video and audio; col. 18, lines 39-56 – various statistics on the timing of frames are monitored; col. 19, lines 11-36 - four situations are determined that include frames being too early and too late).

Regarding claim 57, Subramanian et al. in view of Griffiths discloses all the limitations as previously discussed with respect to claims 20, 28, and 56 including that the two or more succeeding samples to the at least one sample are not consecutive samples (Griffiths: Fig. 11, step 475 - all B frames are dropped regardless of where they are).

Conclusion

5. The prior art made of record and not relied upon is considered pertinent to applicant's disclosure.
- a. Poimboeuf et al. (U.S. Patent 5,764,965) discloses a first timing signal is compared with the system clock to establish a reference. Likewise, the second signal (e.g., audio samples) could be compared with this same system clock to determine its reference. By comparing these two references, it is possible to determine whether the second signal (e.g., audio samples) are aligned with, ahead, or behind in time with respect to the first timing signal (e.g., video stream). Furthermore, one can determine whether the second signal (e.g., audio samples) is running faster, slower, or at the same rate as the first timing signal (e.g., video stream) by comparing their references over a period of time.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to HEATHER R. JONES whose telephone number is (571)272-7368. The examiner can normally be reached on Mon. - Thurs.: 7:00 am - 4:30 pm, and every other Fri.: 7:00 am - 3:30 pm.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Thai Tran can be reached on 571-272-7382. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for

published applications may be obtained from either Private PAIR or Public PAIR.

Status information for unpublished applications is available through Private PAIR only.

For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

Heather R Jones
Examiner
Art Unit 2621

HRJ
September 10, 2009

/Thai Tran/
Supervisory Patent Examiner, Art Unit 2621